

INTRODUCTION

Thank you for choosing a REBOP product. Jet Boost is a high performance effects pedal that delivers a wide range of transparent clean, and sweet, lo-gain overdrive tones.

The pedal offers up to 22dB of signal boost along with Gain and output Level controls. Passive Treble and Bass EQ allows precise, natural voicing while True Bypass switching ensures optimal signal integrity.

A versatile preamp, Jet may be used as a clean boost for solos, to add punch and clarity to rhythm parts or as a permanent boost for guitars with low output pickups. The pedal's soft-clipping Gain stage provides light compression and subtle distortion to fatten the boosted tone. Stacks seamlessly with the Rebob Alfa Drive for a terrific dual-stage overdrive effect.

POWER SUPPLY

The Jet Boost can be powered by a 9V battery or a linear AC mains adaptor. The AC adaptor should provide a regulated 9V DC (NEGATIVE CENTRE PIN) supply and 5.5mm x 2.1mm output jack. If a battery is installed it will be automatically disconnected when an AC adaptor is used.

WARNING! THE USE OF AN AC ADAPTOR THAT DOES NOT MEET THE ABOVE SPECIFICATION MAY DAMAGE THE PEDAL AND VOID YOUR WARRANTY.

BATTERY REPLACEMENT: If the LED indicator is dim or does not illuminate when the pedal is ON, the battery should be replaced. Remove the four screws securing the bottom plate and replace the depleted battery with a new, alkaline 9V PP3 (or equivalent) observing correct polarity. Refit the bottom plate.

WARNING! TO PREVENT DAMAGE DO NOT OPERATE THE PEDAL WITH THE BOTTOM PLATE REMOVED.

OPERATION

1. Connect your guitar to the INPUT. The battery and circuit are active whenever a lead is connected—even if the effect is bypassed—therefore, to prolong battery life, always disconnect the input lead when the pedal is not in use.

CABLING NOTE: Always use high quality, low capacitance screened cables. We recommend that both input and output cables do not exceed 3 metres.

2. Connect the OUTPUT to another pedal or directly to your amplifier.

3. Centre the TREBLE and BASS controls.

4. Turn on the effect by depressing the footswitch (the red LED indicates that the effect is ON).

5. For a clean boost, set the GAIN knob low and use the LEVEL control to increase the input signal to your amplifier. For a mild distortion effect, use a higher GAIN setting, the LEVEL control can then be used to balance your normal and effected sounds.

6. Use the TREBLE and BASS controls to shape the boosted signal.

SPECIFICATIONS

Input Impedance	1M Ohm
Output Impedance	<2K6 Ohm
Power Supply	9V DC
Current Draw	9mA
Bypass	True Hardwire
Dimensions	W68 x H113 x D48mm
Weight	282g

LIMITED WARRANTY

REBOP pedals are guaranteed to be free of defective materials and workmanship for a period of two (2) years from the original date of purchase. Defective products that qualify under this warranty will be repaired or replaced, at the manufacturer's discretion, without charge. This warranty is extended to the original purchaser only and is non-transferable.

To receive warranty service, the product must be returned to the dealer from whom it was purchased or, if the product was purchased direct, shipped carriage pre-paid to our service facility. Before returning a product to us, please submit your service request at www.rebopengineering.com/warranty

This warranty remains valid only if the serial number has not been defaced or removed. It does not cover damage due to accident, misuse, modification, incorrect voltage application or if the product has been repaired or serviced by persons not authorised by the manufacturer. We retain the exclusive right to make such determination on the basis of factory inspection.

REBOP ENGINEERING ASSUMES NO LIABILITY FOR ANY INJURY, LOSS OR DAMAGE, DIRECT OR CONSEQUENTIAL THAT MAY RESULT FROM THE USE OF OR THE INABILITY TO USE THIS PRODUCT.

Please visit www.rebopengineering.com/terms-conditions to view our full Terms & Conditions of Sale.

